

DS-7100HWI-SL Series



Key features

- H.264 & dual-stream video compression
- Full channel@WD1(PAL:960×576,NTSC:960×480) resolution real-time recording
- Alarm for video loss, motion detection, tampering and abnormal signal
- Embedded WEB server for remote access
- Mobile view on 3G/Wifi enabled device (iPhone, Android, Blackberry)

	DS-7104HWI-SL	DS-7108HWI-SL	DS-7116HWI-SL
Video Compression	H.264	H.264	H.264
Video input	4 Channel BNC	8 Channel BNC	16 Channel BNC
Audio input	1 Audio	1 Audio	1 Audio
Outputs Video	CVBS,VGA		
Encoding resolution	WD1 Resolution Real-time		
Frame rate	25 fps (P) / 30 fps (N)		
SATA	1 SATA Each SATA Up to 4TB Capacity	1 SATA Each SATA Up to 4TB Capacity	1 SATA Each SATA Up to 4TB Capacity
Dual-stream	Support; Sub-stream: CIF / QCIF @ 25 fps (P) / 30 fps (N)		
Support DVD/RW	NO		



1. VIDEO IN
2. VIDEO OUT
3. VGA Interface
4. AUDIO IN, RCA Connector
5. AUDIO OUT, RCA Connector
6. LAN Network Interface
7. USB Interface
8. GND
9. 12VDC

