





















ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
1	EZ-IPC-T1B20P-L 	1/2.7" 2Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@1080P (1920×1080) & 25/30fps@1.3MP (1280×960) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC, HLC 3.6mm fixed lens Max. IR LEDs Length 30m Support Smart IR IP67, PoE		15,420,000
2	DH-IPC-T1B20P 	1/2.7" 2Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6mm optional) Max IR LEDs		18,750,000
3	DH-IPC-B1B20P-L 	1/2.7" 2Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@1080P (1920×1080) & 25/30fps@1.3MP (1280×960) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC, HLC 3.6mm fixed lens Max. IR LEDs Length 30m Support Smart IR IP67, PoE		15,420,000
4	DH-IPC-B1B20 	1/2.7" 2Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding 25/30fps@1080P(1920×1080)· DWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer CMS(DSS/PSS) & 2.8 mm fixed lens (3.6mm optional) Max IR LEDs Length 30m IP67, PoE		18,750,000
5	DH-IPC-B2B20-ZS 	1/2.7" 2Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding· 25/30fps@1080P (1920×1080) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8~12mm varifocal lens Max IR LEDs Length 40m Micro SD card memory, IP67, PoE7		26,800,000
6	DH-IPC-D2B20P 	2MP IR Mini-Dome Network Camera 1/2.7" 2Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding· 25/30fps@1080P(1920x1080) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS· 2.8 mm fixed lens (3.6 mm optional) Max IR LEDs Length 30m IP67, PoE		19,730,000









7	IPC-B1A30 EZ-IP	1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding 20fps@3M(2048x1536) &25/30fps@1080P (1920x1080) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens Max. IR LEDs Length 30m IP67, PoE		12,170,000
8	DH-IPC-T1B40P EZ-IP	4MP IR Turret Network Camera · 1/3" 4Megapixel progressive CMOS · H.265+ & H.265 dual-stream encoding · 20fps@4M(2560x1440) &25/30fps@3M(2304x1296) DWDR, Day/Night(ICR) 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6mm optional) Max IR LEDs Length 30m IP67, PoE		21,500,000
9	DH-IPC-T2B20P-ZS EZ-IP	1/2.7" 2Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8~12mm motorized Max IR LEDs Length 40m Micro SD card memory, IP67, PoE		26,800,000
10	DH-IPC-T2B40-ZS EZ-IP	1/3" 4Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding · 20fps@4M(2560x1440) &25/30fps@3M(2304x1296) · DWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer CMS(DSS/PSS) & DMSS 2.8~12mm motorized Max IR LEDs Length 40m Micro SD card memory, IP67, PoE		33,300,000
11	DH-IPC-D2B40P EZ-IP	4MP IR Mini-Dome Network Camera 1/3" 4Megapixel progressive CMOS H.265+ & H.265 dual-stream encoding 20fps@4M (2560x1440) &25/30fps@3M (2304x1296) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.8 mm fixed lens (3.6 mm optional) Max IR LEDs Length 30m IP67, PoE		24,420,000
12	DH-IPC-B1B40P EZ-IP	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M (2560x1440) &25/30fps@3M (2304x1296) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC, HLC 3.6mm fixed lens Max. IR LEDs Length 30m Support Smart IR IP67, PoE		21,500,000
13	DH-IPC-B2B40-ZS EZ-IP	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M (2560x1440) &25/30fps@3M (2304x1296) DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC, HLC 2.8~12mm varifocal lens Max. IR LEDs Length 40m Support Smart IR Micro SD card memory IP67, PoE		29,800,000












14	NVR1A04HS-4P <i>EZ-IP</i>	4 channel IP camera input 1/4/8/9 channel Live Preview H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 Support 4PoE port 100 Mbps Network Card P2P support		17,850,000
15	DH-NVR1B04 <i>EZ-IP</i>	H.265+/H.264+ codec decoding Max 40Mbps/20Mbps incoming/outgoing bandwidth Max 4channel IP camera inputs· Up to 6MP resolution preview&playback Up to 1ch@6MP/4ch@1080P 25fps decoding HDMI/VGA simultaneous video output 1 SATA III Port, up to 4TB capacity for each HDD		20,097,000
16	DH-NVR1B04-4P <i>EZ-IP</i>	H.265+/H.264+ codec decoding Max 4 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support IPC UPnP, 4PoE ports 1 SATA III Port, up to 6TB capacity for each HDD		37,070,000
17	NVR1A08HS <i>EZ-IP</i>	8 channel IP camera input 1/4/8/9 channel Live Preview H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support		11,090,000
18	DH-NVR1B08 <i>EZ-IP</i>	H.265+/H.264+ codec decoding Max 4/8 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output		22,200,000
19	DH-NVR1B08HS <i>EZ-IP</i>	H.265+/H.264+ codec decoding Max 8 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 1 SATA III Port, up to 6TB capacity for each HDD		23,310,000
20	DH-NVR1B08HS-8P <i>EZ-IP</i>	H.265+/H.264+ codec decoding Max 80Mbps incoming bandwidth Max 8 channel IP camera inputs Up to 8MP resolution preview&playback·Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support IPC UPnP, 8PoE ports 1SATA III Port, up to 6TB capacity for each HDD		47,240,000
21	DH-NVR2B16 <i>EZ-IP</i>	16 Channel 1U H.265 Network Video Recorder H.265+/H.264+ codec decoding Max 16 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output		39,600,000








	2 SATA III Ports, up to 6TB capacity for each HDD		
--	---	--	--










<p>1 IPC-PSD81602-A360</p>	<p>8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out 7/2 channel Alarm In/Out RS485 Micro SD memory, IP67, IK10</p>		<p>Call</p>
<p>2 IPC-PSD8802-A180</p>	<p>4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out 7/2 channel Alarm In/Out RS485 Micro SD memory, IP67, IK10</p>		<p>Call</p>
<p>3 IPC-PFW8800-A180</p>	<p>4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/2 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10,PoE+</p>		<p>Call</p>
<p>4 IPC-PFW8601-A180</p>	<p>3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832 3.6mm fixed lens Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/1 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10,PoE+</p>		<p>176,370,000</p>












<p>5 IPC-EBW81230</p>	<p>1/1.7" 12Megapixel progressive scan STARVIST™ CMOS H.265/H.264 triple-stream encoding Max 25fps@12M(4000x3000) Multiple dewarped Mode Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart detection· Intelligent Function Max. IR LEDs length 10m. Micro SD memory, IP67, IK10, PoE 12MP Panoramic Network IR Fisheye Camera</p>		<p>184,750,000</p>
<p>6 IPC-PDBW5831-B360</p>	<p>Four 1/2.8" 2Megapixel progressive scan STARVIST™ CMOS H.265&H.264 dual-stream encoding 25/30fps@2M(1920×1080) Smart Detection supported WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm~12mm motorized lens · Max. IR LEDs Length 30m Micro SD memory, IP67, IK10, PoE+ 4x2MP IR Dome Network Camera</p>		<p>242,970,000</p>
<p>7 IPC-EBW8630P-IVC</p> 	<p>6MP Panoramic Network IR Fisheye Camera 1/1.8" 6Megapixel progressive scan STARVIST™ CMOS· H.265/H.264 triple-stream encoding · Max 25/30fps@6M(3072x2048)· Multiple dewarped Mode· Day/Night(ICR), 3DNR, AWB, AGC, BLC· Smart detection· Intelligent Function· Max. IR LEDs length 10m. Micro SD memory IP67, IK10, PoE Panamorph Lens RPL: B4QQV</p>		<p>173,900,000</p>
<p>8 IPC-PDBW8800-A180</p>	<p>4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIST™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/1 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10,PoE+</p>		<p>Call</p>
<p>9 DHI-ITC237-PW1B-IRZ</p> 	<p>2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -Support plate cutout, overview picture snapshot and video recording -Embedded with White list database,1 ch relay out to control the barrier performance for outdoor applications· 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920×1080) 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB IR Distance 3~8m IP67, IK10, PoE</p>		<p>121,720,000</p>
<p>10 IPC-HFW1230SP-S4</p> <p>New Product</p>	<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE</p>		<p>17,500,000</p>








11	IPC-HFW1230SP-S2	1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens, Max. IR LEDs Length 30m IP67, PoE		18,000,000
12	IPC-HFW1230SP	1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE		18,750,000
13	IPC-HFW1231SP Starlight	1/2.8" 2Megapixel progressive CMOS H.265& H.264 dual-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2.8mm fixed lens Max. IR LEDs Length 30m, Smart IR IP67, PoE Smart Detection (Tripwire Intrusion)		21,700,000
14	IPC-HFW2230SP-S	2MP IR Bullet Network Camera 1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB IP67, PoE, AVI(Tripwire Intrusion)		19,800,000
15	IPC-HFW2231SP-S-S2 New Product Starlight	2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		22,800,000
16	IPC-HFW4231EP-S	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS(Starlight) 3.6mm fixed lens 50/60fps@1080P(1920×1080) H.265+/H.265/H.264+/H.264 triple-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported: Face Detection, Tripwire, Intrusion, Object Abandoned/Missing Max. IR LEDs Length 40m Micro SD card 128GB IP67, PoE		36,000,000
17	IPC-HFW2231TP-ZS	1/2.8" 2Megapixel progressive Starvis™ CMOS H.265 & H.264 dual-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm motorized lens Max IR LEDs Length 60m IP67, IK10(optional), PoE		38,480,000
18	IPC-HFW2231T-ZAS	2MP WDR IR Bullet Network Camera 1/2.8" 2Megapixel progressive Starvis™ CMOS H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 2.7mm~13.5mm, Max. IR LEDs Length 60m, Smart IR Micro SD card memory , 128 GB, Audio I/O 1/1, Alarm I/O 1/1		39,500,000







	IP67, IK10(Optional), PoE, (Tripwire Intrusion Scene Change)		
19	<p>IPC-HFW5231EP-ZE</p> <p></p> <p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 13.5mm motorized lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card memory , 128 GB, Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE, Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		72,000,000
20	<p>IPC-HFW5231EP-Z12E</p> <p></p> <p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 5.3mm ~ 64mm 12x zoom lens 1/1 Audio in/Out 2/1 Alarm In/Out Micro SD card memory , 128 GB Max. IR LEDs Length 200m , Smart IR IP67, IK10, PoE Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		77,000,000
21	<p>IPC-HFW1330SP</p> <p>1/3" 3Megapixel progressive CMOS H.264+ & H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer CMS(DSS/PSS) & DMSS 2.8 mm fixed lens (3.6 mm 6mm optional) Max IR LEDs Length 30m IP67, PoE</p>		22,820,000
22	<p>IPC-HFW1431SP-0360B-S4</p> <p></p> <p>4MP Entry IR Fixed-focal Bullet Network Camera 1/3"4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.03 Lux@F2.0 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE</p>		22,000,000
23	<p>IPC-HFW2431SP-S-S2</p> <p> </p> <p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance: 30 m, Smart IR IP67, PoE</p>		27,300,000
24	<p>IPC-HFW1431SP</p> <p>1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m IP67, PoE</p>		30,220,000









<p>25</p> <p>IPC-HFW4431TP-S-S4</p> <p>New Product</p>	<p>1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4Mp(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens (6mm, 8mm, 12mm optional) Max. IR LEDs Length 80m Micro SD memory 256GB, IP67, IK10, PoE</p>		<p>36,000,000</p>
<p>26</p> <p>IPC-HFW4431EP-SE</p>	<p>1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4M(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens (6mm optional) Max. IR LEDs Length 40m Micro SD memory, IP67, PoE,</p>		<p>39,710,000</p>
<p>27</p> <p>IPC-HFW4431TP-ASE</p>	<p>1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4M(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens (6mm, 8mm, 12mm optional) Max. IR LEDs Length 80m Micro SD memory, IP67, IK10, PoE</p>		<p>41,200,000</p>
<p>28</p> <p>IPC-HFW2431TP-ZS</p>	<p>1/3" 4 Megapixel progressive CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) 2.7mm ~13.5mm motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB Max. IR LEDs Length 60m , Smart IR IP67, PoE+ Smart Detection (Tripwire Intrusion)</p>		<p>46,800,000</p>
<p>29</p> <p>IPC-HFW3441TP-ZS-27135</p> <p>New Product</p> <p>Wiz Sense</p>	<p>4MP IR Vari-focal Bullet WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		<p>55,500,000</p>
<p>30</p> <p>IPC-HFW4431EP-Z-S4</p> <p>New Product</p>	<p>4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive CMOS 2.7mm~13.5mm motorized lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Facedetection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2/1 Alarm in/out, 1/1 audio in/out Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, IK10, PoE</p>		<p>65,000,000</p>
<p>31</p> <p>IPC-HFW5431EP-ZE</p> <p>ePoE</p>	<p>4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25/30fps@4Mp(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m, Smart IR, Micro SD card memory ,128 GB Audio in/Out 1/1, Alarm In/Out 2/1 IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned/Missing Face)</p>		<p>75,000,000</p>











<p>32</p> <p>IPC-HFW5442EP-ZE-0832</p> 	<p>4MP Pro AI IR Vari-focal 1/1.8" 4Megapixel progressive scan CMOS .265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688×1520), 50/60fps@2Mp(1920 × 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lenz, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>		<p>93,000,000</p>
<p>33</p> <p>IPC-HFW2531TP-ZS</p>	<p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB Max IR LEDs Length 60m ,Smart IR IP67, PoE Smart Detection (Tripwire Intrusion)</p>		<p>50,810,000</p>
<p>34</p> <p>IPC-HFW4631EP-SE</p> 	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6M(3072x2048), 25/30fps@4M(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 40m Micro SD card memory , 128 GB IP67, PoE Smart Detection (Tripwire Intrusion Object Abandoned Missing Face)</p>		<p>46,870,000</p>
<p>35</p> <p>IPC-HFW5631EP-ZHE</p> 	<p>1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 Triple-stream encoding 20fps@6M(3072×2048),25/30fps@4M(2688×1520) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 7mm~35mm(5x zoom) Motorized lens Max. IR LEDs Length 100m, Micro SD card memory , 128 GB 2/1 Alarm in/out, 1/1 audio in/out, IP67, IK10, PoE(Tripwire Intrusion Object Abandoned Missing Face)</p>		<p>89,000,000</p>
<p>36</p> <p>IPC-HFW1831EP</p>	<p>8MP WDR IR Mini Bullet Network Camera 1/1.8" 8Megapixel progressive scan CMOS H. 265&H.264 dual-stream encoding 25/30fps@8MP(3840×2160) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (4mm, 6mm optional) Max. IR LEDs Length 50m IP67, PoE</p>		<p>48,100,000</p>
<p>37</p> <p>IPC-HFW2831T-ZS</p>	<p>8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265/H.264 codec, MJPEG, high compression rate, ultra- low bit rate 8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm–13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		<p>56,000,000</p>















<p>38</p> <p>IPC-HFW4831EP-SE</p> <p></p>	<p>1/2.5" 8Megapixel progressive scan CMOS H.265+&H.265&H.264&MJPEG triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens Max. IR LEDs Length 40m Micro SD card memory , 128 GB IP67, PoE Smart Detection (Tripwire Intrusion Scene Change Face)</p>		<p>58,340,000</p>
<p>39</p> <p>IPC-HFW2831TP-ZS</p>	<p>8MP WDR IR Bullet Network Camera 1/1.8" 8Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 3.7~11mm motorized lens Max IR LEDs Length 60m IP67, IK10(optional), PoE</p>		<p>68,900,000</p>
<p>40</p> <p>IPC-HFW5831EP-ZE</p> <p></p>	<p>1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) 2.7mm ~12mm motorized lens Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE Smart Detection (Tripwire Intrusion Object Abandoned Missing Face)</p>		<p>92,600,000</p>
<p>41</p> <p>IPC-K100W</p> <p></p> <p>New Product</p>	<p>1/3" 1.3Megapixel Aptina CMOS H.264 & MJPEG dual-stream encoding Max 15fps@1.3M (1280×960)/25/30fps@720P(1280×720) DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens White LEDs length 10m PIR sensor range 6m Micro SD memory Wi-Fi</p>		<p>21,200,000</p>
<p>42</p> <p>IPC-K200W</p> <p></p> <p>New Product</p>	<p>1/3" 2Megapixel progressive scan CMOS H.264 & MJPEG dual-stream encoding Max 25/30fps@1080P(1920×1080) DWDR, Day/Night, 3DNR, Auto iris, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens White LEDs length 10m PIR sensor range 6m Wi-Fi</p>		<p>32,930,000</p>
<p>43</p> <p>IPC-HDW1230T1P-S4</p> <p>New Product</p>	<p>2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR IP67, PoE</p>		<p>16,300,000</p>
<p>44</p> <p>IPC-HDW1230SP</p>	<p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p>		<p>18,000,000</p>






45	IPC-HDBW1230EP	1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, IK10, PoE		18,500,000
46	IPC-HDW2231TMP-AS-S2 New Product	2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		23,800,000
47	IPC-HDW2231TP-AS	2MP, 1/2.8" CMOS image sensor, low illuminance, high image Outputs max. 2MP (1920 × 1080) @25/30 fps.STARLIGHT· H.265 codec, high compression rate, ultra-low bit rate· Built-in IR LED, max. IR distance: 30 m· ROI, SMART H.264/H.265, flexible coding, applicable to various· Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking,· Intelligent detection: Intrusion, tripwire· Abnormality detection: Motion detection, video tampering, · Supports max. 256 GB Micro SD card, built-in Mic· 12V DC/PoE power support · IP67 protection		30,830,000
48	IPC-HDW4231EMP-ASE NEW Product	1/2.8" 2Megapixel progressive scan STARVISTM CMOS H.265&H.264 triple-stream encoding· 50/60fps@1080P(1920×1080) Smart detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS· 2.8mm fixed lens (3.6mm,6mm optional) Built-in Mic Max. IR LEDs Length 50m Micro SD memory, IP67, PoE		35,520,000
49	IPC-HDW2231RP-ZS	1/2.8" 2Megapixel progressive StarvisTM CMOS H.265& H.264 dual-stream encoding STARLIGHT 25/30fps@1080p(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS· Micro SD card slot, up to 128GB IP67, PoE· 2.7~13.5mm motorized lens Max IR LEDs Length 50m		38,230,000
50	IPC-HDBW1320EP	3MP IR Mini-Dome Network Camera 1/3" 3Megapixel progressive CMOS H.264+ & H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & 2.8 mm fixed lens (3.6 mm optional)· Max IR LEDs Length 30m IP67, IK10, PoE		22,820,000
51	IPC-HDW1431T1P-0280B-S4 New Product	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4Megapixel progressive CMOS 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE		20,500,000






<p>52</p> <p>IPC-HDW2431TMP-AS-S2</p> <p>New Product</p> <p>Starlight</p>	<p>4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE</p>		<p>26,200,000</p>
<p>53</p> <p>IPC-HDBW2431EP-S-S2</p> <p>Starlight</p>	<p>4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE</p>		<p>27,300,000</p>
<p>54</p> <p>IPC-HDBW1431EP</p>	<p>1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m IP67, IK10, PoE</p>		<p>30,590,000</p>
<p>55</p> <p>IPC-HDW1431SP</p>	<p>1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m IP67, PoE</p>		<p>27,500,000</p>
<p>56</p> <p>IPC-DW4431EMP-AS-S4</p> <p>New Product</p>	<p>4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>		<p>31,000,000</p>
<p>57</p> <p>IPC-HDW3441TMP-AS-0280B</p> <p>New Product</p> <p>Wiz Sense</p>	<p>4MP IR Fixed focal Eyeball WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>		<p>34,000,000</p>

<p>58</p> <p>IPC-HDBW4431EP-ASE</p> 	<p>4MP IR mini Dome Network Camera 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4M(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm, 6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 30m Micro SD memory, IP67, IK10, PoE</p>		<p>38,230,000</p>
<p>59</p> <p>IPC-HDBW4431EP-S</p>	<p>1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4Mp(2688×1520) Smart Detection supported· WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm, 6mm optional) Max. IR LEDs Length 30m Micro SD memory 256GB, IP67, IK10, PoE</p>		<p>37,000,000</p>
<p>60</p> <p>IPC-HDW4431EMP-ASE</p> 	<p>1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4M(2688×1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm,6mm optional), Built-in Mic Max. IR LEDs Length 50m Micro SD memory IP67, PoE</p>		<p>39,710,000</p>
<p>61</p> <p>IPC-HDBW2431RP-ZAS-S2</p> <p>New Product</p> <p>Starlight</p>	<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7~13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>		<p>45,000,000</p>
<p>62</p> <p>IPC-HDBW2431RP-ZS</p>	<p>4MP WDR IR Dome Network Camera H.265 & H.264 dual-stream encoding· 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC· Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 2.7~13.5mm varifocal lens· Max IR LEDs Length 30m IP67, IK10, PoE</p>		<p>48,720,000</p>
<p>63</p> <p>IPC-HDBW5431RP-ZE</p>	<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive scan CMOS· H.265&H.264 triple- stream encoding 25/30fps@4Mp(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m· Micro SD card memory IP67,IK10, PoE+</p>		<p>72,800,000</p>





<p>64</p> <p>IPC-HDW5431RP-ZE</p> 	<p>4MP WDR IR Eyeball Network Camera 1/3" 4Megapixel progressive scan CMOS H.265&H.264 triple-stream encoding 25/30fps@4Mp(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m Micro SD card memory, IP67, PoE</p>		<p>72,800,000</p>
<p>65</p> <p>IPC-HDBW5431EP-Z-H</p>	<p>1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding Max 20fps@4Mp(2560×1440), 25/30fps@3M(2304×1296) WDR (120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens, Max. IR LEDs Length 50m IP67, IK10, PoE, Micro SD card memory, 128 GB Audio in/Out, Alarm In/Out Smart Detection (Tripwire Intrusion Scene Change Face)</p>		<p>75,000,000</p>
<p>66</p> <p>IPC-HDBW5442EP-ZE</p>	<p>4MP IR Vari-focal Dome WizMind Network Camera 1/1.8" 4Megapixel progressive scan CMOS ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments 25/30 fps@2688 × 1520, 50/60 fps@1080P (1920 × 1080) WDR (140 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS 2.7 mm-12.0 mm motorized lens 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 40 m Micro SD memory, IP67, IK10</p>		<p>88,500,000</p>
<p>67</p> <p>IPC-HDW2531RP-ZS</p>	<p>1/2.7" 5Megapixel progressive CMOS H.265& H.264 dual-stream encoding 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & · Micro SD card slot, up to 128GB 2.7~13.5mm motorized lens Max IR LEDs Length 50m· IP67, PoE</p>		<p>50,570,000</p>
<p>68</p> <p>IPC-HDBW2531RP-ZAS</p>	<p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Mirco SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67,IK10, PoE</p>		<p>51,800,000</p>
<p>69</p> <p>IPC-HDW4631EM-ASE</p> 	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H.265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Built-in MicMax. IR LEDs Length 50m, Smart IR Micro SD card memory , 128 GB, IP67, PoE (Tripwire Intrusion Object Abandoned/Missing Face)</p>		<p>44,000,000</p>
<p>70</p> <p>IPC-HDBW4631EP-ASE</p> 	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H.265&H.264 triple-stream encoding: 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) Smart Detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm optional) 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 30m Micro SD memory, IP67, IK10, PoE</p>		<p>46,250,000</p>

<p>71</p> <p>IPC-HDW4631EMP-ASE</p> 	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H.265&H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) Smart detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens (3.6mm optional)· Built-in Mic Max. IR LEDs Length 50m Micro SD memory, IP67, PoE</p>		<p>46,870,000</p>
<p>72</p> <p>IPC-HDW5631RP-ZE</p>  	<p>1/2.9" 6Megapixel progressive scan CMOS H.265&H.264 dual-stream encoding 20fps@6M(3072x2048),25/30fps@4M(2688x1520) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens Built-in Mic Max. IR LEDs Length 50m Micro SD card memory, IP67, PoE</p>		<p>79,500,000</p>
<p>73</p> <p>IPC-HDBW5631EP-ZE</p> 	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H.265&H.264 dual-stream encoding 20fps@6M(3072x2048),25/30fps@4M(2688x1520) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m Micro SD card memory IP67,IK10, PoE+</p>		<p>81,300,000</p>
<p>74</p> <p>IPC-HDBW5831RP-ZE</p>	<p>8MP WDR IR Dome Network Camera 1/2.5" 8Megapixel progressive scan STARVISTM CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840x2160),25/30fps@3M(2304x1296) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens Max. IR LEDs Length 50m Micro SD card memory, IP67,IK10, PoE</p>		<p>90,500,000</p>
<p>75</p> <p>IPC-HDBW8630EP-ZE</p> 	<p>1/1.8" 6Megapixel progressive scan STARVISTM CMOS H.265&H.264 triple-stream encoding 25/30fps@6M(3072x2048) DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 4.1~16.4mm motorized Max. IR LEDs Length 50m Micro SD memory,IP67,IK10,PoE+</p>		<p>159,720,000</p>
<p>76</p> <p>IPC-HDBW4831EP-ASE</p> 	<p>1/2.5" 4K 8Megapixel progressive scan Starvis CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840x2160),25/30fps@3Mp (2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens Max. IR LEDs Length 30m Alarm in/out, Audio in/out Micro SD card memory , 128 GB IP67,IK10, PoE Smart Detection (Tripwire Intrusion Scene Change Object Abandoned/Missing Face)</p>		<p>58,340,000</p>
<p>77</p> <p>IPC-HDW4831EMP-ASE</p> 	<p>1/2.5" 4K 8Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840x2160),25/30fps@3Mp(2304x1296) WDR (120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens Max. IR LEDs Length 50m Built-in Mic Micro SD card memory , 128 GB IP67, PoE Smart Detection (Tripwire Intrusion Scene Change Object</p>		<p>58,340,000</p>

		Abandoned/Missing Face)		
78	IPC-HDBW2831RP-ZS	8MP WDR IR Dome Network Camera 1/1.8" 8Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Micro SD card slot, up to 128GB 3.7~11mm motorized lens Max IR LEDs Length 30m IP67, IK10, PoE		68,900,000
79	IPC-HDW5831RP-ZE	1/2.5" 8Megapixel progressive scan CMOS H.265&H.264 dual-stream encoding 15fps@4K(3840×2160),25/30fps@3M(2304×1296) Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens· Built-in Mic Max. IR LEDs Length 50m Micro SD card memory, IP67, PoE		90,500,000
80	IPC-HDBW5831EP-ZE	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3M(2304×1296) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 12mm motorized lens 1/1 Audio in/Out 1/1 Alarm In/Out Micro SD card memory , 128 GB Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE+ Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)		88,00,000
81	SD1A203T-GN	1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 2.7mm ~ 8.1mm , 3x Optical Zoom Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Support Defog IR Distance up to 15m, IP 66, support POE Smart Detection (Tripwire Intrusion Abandoned/Missing Face Detection)		53,000,000
82	SD29204T-GN	1/2.7" 2MP CMOS Sensor H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 2.7mm ~ 11mm , 4x Optical Zoom Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic IR Distance up to 30m, support POE Smart Detection (Tripwire Intrusion Scene Change Face Abandoned-Missing Object)		49,700,000

<p>83 SD29204UE-GN</p>	<p>1/2.8" STARVIS™ CMOS . STARLIGHT Powerful 4x optical zoom Support Triple-streams encoding WDR, Day/Night(ICR), Ultra DNR Max. 25/30fps@1080P, IVS Support PoE IR distance up to 30m</p>		<p>64,800,000</p>
<p>84 SD49225T-HN-S2 New Product Starlight</p>	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6)B/W:(0.0005Lux@F1.6) Max. 25/30fps@1080P, 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR,BLC, HLC, AWB, AGC, ROI Support Defog IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, 1/1 Audio in/out Support PoE+, IR Distance up to 100m, IP66</p>		<p>122,000,000</p>
<p>85 SD49225T-HN-W</p>	<p>1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom Starlight technology Max. 25/30fps@1080P IVS. 2MP 25x Starlight IR PTZ Wi-Fi Network Camera Support Wifi IR distance up to 100m· IP66</p>		<p>118,700,000</p>
<p>86 SD49225XA-HNR</p>	<p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		<p>133,000,000</p>
<p>87 SD59225U-HNI</p>	<p>2MP 25x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.8mm~120mm 25x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+ IR Distance up to 150m IP66,OSD</p>		<p>148,000,000</p>



<p>88 SD6CE225U-HNI</p>	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P 4.8mm~120mm 25x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR (120dB), Day/Night (ICR), Ultra DNR, BLC, HLC Support Defog, ROI, EIS Auto-tracking and IVS (Tripwire, Intrusion, Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 Alarm 7/2 in/out, Audio 1/1 in/out IR Distance up to 200m PoE+, IP67, IK10</p>		<p>158,000,000</p>
<p>89 SD6CE230U-HNI</p>	<p>1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out, Audio 1/1 in/out 1*Video output, RS485, IR Distance up to 200m PoE+, IP67, IK10</p>		<p>237,000,000</p>
<p>90 SD59230U-HNI Starlight</p>	<p>2MP 30x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.5mm~135mm 30x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection) Support Defog and EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out Audio 1/1 in/out Support PoE+ IR Distance up to 150m IP66, OSD</p>		<p>221,000,000</p>
<p>91 SD6AL245U-HNI</p>	<p>2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS Powerful 45x optical zoom Max. 50/60fps@1080P Auto tracking and IVS Support Hi-PoE IR distance up to 300m IP67</p>		<p>492,100,000</p>






<p>92 SD60230T-HN</p>	<p>1/2.8" 2Mp CMOS Sensor H.264+/H.264 Encoding, Ultra-low bit rate transmission Max. 30fps@1080P(2592×1520) & 60fps @720P resolution DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 600°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out Alarm In/Out IP67,IK10, POE+ Smart Detection (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)</p>		<p>Call</p>
<p>93 SD6CE245U-HNI Starlight</p>	<p>2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10</p>		<p>267,630,000</p>
<p>94 SD65F230F-HNI Super Starlight</p>	<p>1/1.9" 2MP CMOS Sensor(Super Starlight) H.264 / MJPEG Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P 6mm~180mm Powerful 30x optical zoom Max 300°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out Audio 1/1 in/out 1 video output RS485 IR Distance up to 100m Support PoE+ IP66,IK10</p>		<p>Call</p>
<p>95 SD59430U-HNI</p>	<p>1/3" 4Megapixel CMOS H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate transmission Max. 25/30fps@4M(2592×1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out Alarm In/Out IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)</p>		<p>252,220,000</p>

<p>96</p> <p>SD59432XA-HNR</p> <p>New Product</p> <p>Starlight</p> <p>Wiz Sense</p>	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Min. Illumination:Color(0.005Lux@F1.3)B/W(0.0005Lux@F1.3) Max. 25/30fps@4M 4.9 mm–156 mm Focal Length, 32x optical zoom Deep-learning-based auto tracking and perimeter protection(Recognition of human and vehicle) IVS(Tripwire, intrusion, Object abandoned/missing, Face Detection) WDR(120dB), Day/Night(ICR), Ultra DNR, AWB, AGC, BLC, HLC Support Defog and EIS , RoI Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66</p>		<p>295,000,000</p>
<p>97</p> <p>IPC-PF83230-A180</p>	<p>Four 1/1.8" 8Megapixel progressive scan CMOS H.265/H.264 triple-stream encoding Max 25fps@8640x3840 Support 180-degree panoramic view Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD memory, IP67, IK10 4x8MP Multi-Sensor Panoramic Bullet Network Camera</p>		<p>1,048,330,000</p>
<p>98</p> <p>NVR104-P</p>	<p>4CH Smart Box 4PoE Network Video Recorder Up to 4 channel IP camera input H.264/MJPEG dual codec decoding Max 56Mbps incoming bandwidth HDMI/VGA simultaneous video output All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan)</p>		<p>20,000,000</p>
<p>99</p> <p>NVR108-P</p>	<p>8CH Smart Box 4PoE Network Video Recorder Up to 8 channel IP camera input H.264/MJPEG dual codec decoding Max 56Mbps incoming bandwidth HDMI/VGA simultaneous video output All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan)</p>		<p>26,50,000</p>
<p>100</p> <p>NVR2104HS-4KS2</p>	<p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		<p>20,350,000</p>
<p>101</p> <p>NVR4104HS-4KS2</p>	<p>4 Channel Compact 1U 4K&H.265 Lite Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback Up to 2ch@4K/8ch@1080P decoding HDMI/VGA simultaneous video output 1 SATA III Port Up to 6 TB capacity for each HDD</p>		<p>29,600,000</p>
<p>102</p> <p>NVR4104HS-P-4KS2</p>	<p>Smart H.265+/H.265/Smart H.264+/H.264 Max 80Mbps Incoming Bandwidth Support IPC UPnP, 4PoE ports Up to 8MP Resolution for Preview and Playback Up to 2ch@4K/8ch@1080P decoding HDMI/VGA simultaneous video output 1 SATA III Port Up to 6 TB capacity for each HDD</p>		<p>43,700,000</p>



103	NVR2104HS-P-4KS2	<p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card 4PoE Port P2P support</p>		32,680,000
104	NVR2108HS-4KS2	<p>8 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support</p>		23,680,000
105	NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support</p>		32,070,000
106	NVR2108HS-8P-4KS2	<p>8 channel IP camera input. H.265/H.264 codec decoding Max 80Mbps incoming bandwidth. Up to 8Mp resolution preview&playback. Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0. 100 Mbps Network Card 8Port PoE P2P support</p>		42,500,000
107	NVR4108HS-8P-4KS2	<p>8 Channel Compact 1U 8PoE 4K&H.265 Lite Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback Up to 2ch@4K/8ch@1080P decoding HDMI/VGA simultaneous video output Support IPC UPnP, 8PoE ports</p>		52,500,000
108	NVR4116HS-4KS2	<p>16 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support</p>		39,400,000
109	NVR4216-4KS2	<p>16 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card</p>		56,500,000



		P2P support		
110	NVR5216-4KS2	16Channel 1U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback HDMI/VGA simultaneous video output 2 SATA III Ports, Up to 10 TB capacity for each HDD		76,470,000
111	NVR4216-16P-4KS2	16 Channel 1U 16PoE 4K&H.265 Lite Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 Max 200Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback Up to 2ch@4K/8ch@1080P decoding HDMI/VGA simultaneous video output Support IPC UPnP, 16PoE ports. 2 SATA III Ports, Up to 6 TB capacity for each HDD		98,000,000
112	NVR5416-4KS2	16Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback 2HDMI/2VGA simultaneous video output 4 SATA III Ports, Up to 10 TB capacity for each HDD		122,100,000
113	NVR5216-16P-4KS2	16Channel 1U 16PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback HDMI/VGA simultaneous video output 1-8 PoE Ports Support 800m ePoE & EoC 2 SATA III Ports, Up to 10 TB capacity for each HDD		127,900,000
114	NVR5416-16P-4KS2E	16Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback 2HDMI/2VGA simultaneous video output 1-8 PoE Ports Support 800m ePoE & EoC. 4 SATA III Ports, Up to 8 TB capacity for each HDD		175,130,000
115	NVR5216-16P-I	16Channel 1U 16PoE AI Network Video Recorder 16 Channel IP video access Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Up to 16 Channel perimeter protection Up to 4 Channel video stream face recognition Up to 24 face pictures /sec processing Up to 20 face databases with 100,000 face images in total 1-8 PoE Ports support ePoE & EoC		365,070,000
116	NVR5224-24P-4KS2	24Channel 1U 24PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback Support IPC UPnP, 24 PoE ports 3D intelligent positioning with Dahua PTZ camera. 2 SATA III Ports, Up to 8 TB capacity for each HDD		175,130,000
117	NVR5424-24P-4KS2	24Channel 1.5U 24PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback Support IPC UPnP, 24 PoE ports 24Channel 1.5U 24PoE 4K&H.265 4 SATA III Ports, Up to 8 TB capacity for each HDD		203,500,000



118	NVR4232-4KS2	<p>32 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card P2P support</p>		61,000,000
119	NVR4432-4KS2	<p>32 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 4 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 16 Alarm Input, 4 Relay Output RS232 , RS485 2*10/100/1000Mbps Mbps Network Card P2P support</p>		85,000,000
120	DHI-NVR5232-4KS2(V2.0) New Product	<p>32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card RS232, RS485,4/2 Alarm In/out , P2P Support</p>		94,500,000
121	NVR5232-4KS2	<p>32 channel IP camera input 32 channel Live Preview Up to 12Mp resolution preview&playback Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps incoming bandwidth Record Rate 320 Mbps Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding HDMI/VGA simultaneous video output 16 channel playback Support 2 SATA HDDs up to 20TB, 2 USB(1 USB3.0) 1000 Mbps Network Card RS232, RS485 4 Alarm Input, 2 Relay Output Support P2P</p>		103,600,000
122	NVR4832-4KS2	<p>32 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 8 SATA HDD up to 6TB 3 USB Ports (2 USB2.0, 1 USB3.0) 16 Alarm Input, 4 Relay Output RS232 , RS485 2*10/100/1000Mbps Mbps Network Card P2P support</p>		139,000,000
123	NVR5432-4KS2(V2.0) New Product	<p>32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)</p>		145,000,000

		Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out P2P Support		
124	NVR5432-4KS2	32 channel IPC input 32 channel Live Preview Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2 HDMI/VGA simultaneous video output Support 4 SATA HDDs up to 40TB, 3 USB(1 USB3.0, 2USB2.0) Support 1 e-SATA 2*1000 Mbps Network Card RS232, RS485 16 Alarm In , 6 Relay Output P2P Support		142,000,000
125	NVR5432-16P-4KS2	32 Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output 3D intelligent positioning with PTZ camera		195,240,000
126	NVR5832-4KS2	32 channel IPC input 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card RS232 16 Alarm In , 6 Relay Output P2P Support Raid 0/1/5/6/10		217,560,000
127	NVR608-32-4KS2	Intel Dual-core Processor 32 channel IPC input 32 Channel Live Preview: (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card RS232 , RS485 16 Alarm In , 8 Relay Output		221,260,000
128	DHI-NVR5464-4KS2(V2.0) New Product	64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support		169,000,000

129	DHI-NVR5864-4KS2(V2.0) New Product	64 Channel 2U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support		254,000,000
130	NVR608-64-4KS2	Intel Quad-core Processor 64 channel IPC input 32 Channel Live Preview: (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card RS232 , RS485 16 Alarm In , 8 Relay Output		368,770,000
131	DHI-NVR608-128-4KS2 New Product	128 Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA Port Support Raid 0/1/5/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output		470,000,000
132	ESS1508C	2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection		78,000,000
133	PFS3006-4ET-60	4-Port Fast Ethernet PoE Switch Layer two commercial switch 2*10/100 Mbps Uplink ports 4*10/100 Mbps PoE ports Port1≤60W, Port2-4≤30W, Total≤60W Support IEEE802.3af, IEEE802.3at(PoE+) ,Hi PoE 1.8Gbps Switching Capacity 890Kpps Mpps Packet Forwarding Rate 768Kb Packet Buffer Memory MAC atable size is 2K Supports DC 48-57V power supply		11,700,000
134	DH-PFS3106-4ET-60	4-Port PoE Switch (Unmanaged) Layer two Hardened PoE switch Supports PoE power management MAC auto learning and aging, MAC address capacity is 8K Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Wide working temperature design: -30°C~ 65°C Supports dual power backup		19,610,000

<p>135 DH-PFL-2106-4ET-96</p>	<p>4-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Two-layer industrial PoE switch MAC auto study and aging, MAC address list capacity is 8K Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard Industrial wide temperature design</p>		<p>32,680,000</p>
<p>136 PFS3010-8ET-96</p>	<p>8-Port Fast Ethernet PoE Switch Layer two commercial switch 2*10/100/1000 Mbps Ports 8*10/100 Mbps PoE Ports Port1≤60W, Port2-8≤30W, Total≤96W Support IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE 5.6Gbps Switching Capacity 4.17 Mpps Packet Forwarding Rate 4Mb Packet Buffer Memory MAC Table Size is 16K Supports DC 48-57V power supply</p>		<p>24,540,000</p>
<p>137 PFS3110-8P-96</p>	<p>8-Port PoE Switch (Unmanaged) Layer two Hardened PoE switch Supports PoE power management MAC auto learning and aging, MAC address capacity is 8K Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1-2 supports Hi-PoE 60W power supply Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Wide working temperature design: -30°C~ 65°C Supports dual power backup</p>		<p>26,700,000</p>
<p>138 DH-LR-2110-8ET-120</p>	<p>8-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Layer-two ePoE switch MAC auto study and aging, MAC address list capacity is 8K Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard Industrial wide temperature design Port indicator light is to display the status of current transmission mode for the port, which includes IEEE, E100 and E10</p>		<p>51,180,000</p>
<p>139 PFS4218-16ET-190</p>	<p>Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤190W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity 5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		<p>67,500,000</p>
<p>140 PFS4218-16ET-240</p>	<p>Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity 5.36 Mpps Packet Forwarding Rate Network Management by WEB (http and https protocol)</p>		<p>85,100,000</p>

<p>141 DH-LR-2218-16ET-240</p>	<p>16-Port ePoE Switch· Supports long distance PoE transmission up to 800m with ePoE technology of Dahua· Layer-two web managed ePoE switch· Port 1-8 support three self-adaptive transmission modes which are IEEE, E100 and E10· Port 1-8 support both twisted-pair transmission and coaxial cable transmission· Support web management: port management, 802.1Q VLAN, STP/RSTP, LACP, 802.1X, QoS · Support PoE management, Green PoE, Legacy Support· Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards</p>		<p>104,830,000</p>
<p>142 PFS4226-24ET-240</p>	<p>24-Port PoE Switch Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity 6.55 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		<p>97,000,000</p>
<p>143 PFS4226-24ET-360</p>	<p>24-Port PoE Switch Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤360W Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Support Web management management, PoE Setting/Event Statistics/Green PoE Non-blocking video transmission</p>		<p>96,700,000</p>
<p>144 PFS4226-24GT-360</p>	<p>24-Port PoE Gigabit Managed Switch Layer 2 network management PoE switch 24*10/100/1000 Base-T (PoE power supply) 2*100/1000 Base-X, Port1/2 support Hi-PoE (60W) Each power ≤30W, PoE Budget≤360W Spanning tree: STP/RSTP/MSTP Network management based on SNMP Configuration: Web, Telnet, CLI Command Support Vlan:VLAN/802.1Q Standard Vlan, 8K MAC Table 52G Switching Capacity, 38.688 Mpps Packet Forwarding Rate EMC high protection design</p>		<p>123,000,000</p>
<p>145 PFT1300</p>	<p>PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption ≤8W), maxtransmission distance 300m</p>		<p>5,150,000</p>

146 PFM700	*1 Channel HDMI Transmission Signal *1080P/1080I/720P/576P/576I/480P/480I Resolution Output Signal *60M (max)Transmission Distance *Input voltage DC5V *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal:support HDMI 1.3		14,400,000
147 DHI-NKB1000	Keyboard to Control : -Dahua High Speed Dome (all models) -Dahua Standalone DVR -Dahua Network High Speed Dome -Network Video Server Connection : RS485, RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB		71,000,000

TEL : 54424000